

MIGHTY

LINE

Lightweight, industrial-strength stepladder



NO TOP CAP ACCESS

Removal of top rung inhibits users from standing on top cap and encourages safe use

INNOVATIVE TOP CAP

WORK FASTER WITH LESS FOOT FATIGUE

Wide, comfortable standing platform

AVOID INJURIES FROM MISSING THE BOTTOM RUNG

Patent-Pending Ground Cue® indicator alerts user to last step



Patent-pending, shock-absorbing brace and rail shield

PATENT-PENDING HI-VIZ GREEN

NONCONDUCTIVE FIBERGLASS SIDE RAILS



Little Giant
Ladder Systems

CLIMB ON



Heel-to-toe foot support on wide standing platform



Slim profile, easy to store



Easy transport and handling

We designed the Little Giant® MightyLite™ to address the three leading types of stepladder injuries:

1. Painful shoulder, neck, and back injuries from carrying heavy equipment
2. Dangerous falls from standing on the top rung or top cap
3. Ankle, knee, and back injuries from missing the bottom step while descending the ladder

First, the MightyLite is **significantly lighter** than any comparable traditional stepladder. Second, the MightyLite's design helps to **prevent users from standing on the top step**, the most common cause of severe stepladder falls. Third, the MightyLite's patent-pending Ground Cue® prevents injuries by signaling the user when it is **safe to dismount the ladder**.

The MightyLite's platform design opens easily from a slim 4" storage profile and offers wide, comfortable treads on each step, with a very spacious, comfortable standing deck. Its convenient top cap allows you to keep all of your tools close at hand—no more trips up and down the ladder for tools or hardware. The Little Giant MightyLite is available in both Grade 1A 300 lbs and Grade 1AA 375 lbs ratings.

1-YEAR LIMITED WARRANTY

Part Number	Model	Grade	Highest Standing Level	Max Reach*	Spread	Step Width	Storage Height	Storage Width	Storage Depth	Weight
15364-303	4'	1A	1' 10.5"	8' 4.5"	2' 3.5"	3.25"	4' 2"	1' 7"	4"	12 lbs
15384-303	4'	1AA	1' 10.5"	8' 4.5"	2' 3.5"	3.25"	4' 2"	1' 7"	4"	13 lbs
15365-303	5'	1A	2' 10"	9' 4"	2' 11"	3.25"	5' 2"	1' 8.5"	4"	14 lbs
15385-303	5'	1AA	2' 10"	9' 4"	2' 11"	3.25"	5' 2"	1' 8.5"	4"	16 lbs
15366-303	6'	1A	3' 9.5"	10' 3.5"	3' 7"	3.25"	6' 2"	1' 10"	4"	17 lbs
15386-303	6'	1AA	3' 9.5"	10' 3.5"	3' 7"	3.25"	6' 2"	1' 10"	4"	19 lbs
15368-303	8'	1A	5' 8"	12' 2"	4' 11"	3.25"	8' 2"	2'	4"	24 lbs
15388-303	8'	1AA	5' 8"	12' 2"	4' 11"	3.25"	8' 2"	2'	4"	25 lbs

*A 5' 6" person with a 12" vertical reach

Comfort Step 13" x 13"

Initial: _____ **Date:** V.C.R.

- Colors
- Type
- Logo
- Warranty
- Duty Rating/Type
- Nonconductive
- Spec Box
 - Dieline
 - Dimensions
 - Fold lines
 - Diecuts
 - Active
 - Bleed
 - Color call out
 - Print material
 - Date
- Ladder Spec Box
 - Guideline Requirements
- Images
 - Hero
 - Lifestyle(s)

Initial: CP **Date:** 3.9.18
M-D-YR

- Verbage
 - Approved grammar
 - Callout(s)/Description(s)
 - Typos
- Logo & Product
 - Trademark/Registered
- UPC/QR Code
- Warranty
- Duty Rating/Type
- Nonconductive
- Spec Box
 - Version
 - Printing Co
 - File name
 - Date
- Ladder Spec Box
 - Order
 - Accuracy
- Images
 - Hero
 - Lifestyle(s)
- Callout(s)/Description(s)
- Grammar

B. Moss BSM Date: 3-9-18
 T. Hartman TH Date: 3-12
 Executive(s) _____ Date: _____
 _____ Date: _____
M-D-YR

