

Little Giant® Ladder Systems

VELOCITY®

MULTI-POSITION LADDER | TYPE IA | 300 LBS RATED | OSHA + ANSI COMPLIANT

1 LADDER, ∞ JOBS.

1. MULTI-POSITION LADDER

Multi-position ladder easily converts to A-frame, extension, 90-degree, staircase and trestle-and-plank* scaffolding configurations.

2. ROCK LOCK®

Easy-to-use Rock Lock® adjusters move the inner section of the ladder to the height you need.

3. TIP & GLIDE™ WHEELS

Tip & Glide™ wheels allow for smooth ladder transportation.

4. TWO-PERSON STEPLADDER

Meets or exceeds all OSHA and ANSI standards. In A-frame position, it holds 300 lbs on both sides.

*Trestle brackets and Plank™ sold separately.





A-Frame



90-Degree



Extension



Tip & Glide™ Wheels



Storage Position



Rock Locks®

PRODUCT DESCRIPTION

The Velocity® ladder meets or exceeds all OSHA and ANSI standards and is rated Type IA to hold 300 lbs. If you need a rugged, do-it-all ladder, it is the perfect piece of climbing equipment. This lightweight, multi-position ladder will help you get stuff done faster and more efficiently than the average stepladder.

LIMITED LIFETIME WARRANTY

Part #	Model	Stepladder Size Min-Max	Stepladder Highest Standing Level Min-Max	Stepladder Max Reach*	Extension Size Max	Extension Highest Standing Level Min-Max	Extension Max Reach*	Storage Height	Storage Depth	Weight
15413-001	13'	3' 6" - 5' 6"	0' 11" - 2' 11"	9' 5"	11'	3' 9" - 7' 9"	14' 3"	3' 7"	8"	34 lbs
15417-001	17'	4' 6" - 7' 6"	1' 11" - 4' 10"	11' 3"	15'	5' 9" - 11' 7"	18' 1"	4' 7"	8"	41 lbs
15422-001	22'	5' 6" - 9' 6"	2' 11" - 6' 8"	13' 1"	19'	7' 10" - 15' 6"	22'	5' 7"	8"	49 lbs
15426-001	26'	6' 6" - 11' 6"	3' 10" - 8' 7"	15' 1"	23'	9' 9" - 19' 4"	25' 10"	6' 7"	8"	57 lbs

*A 5' 6" person with a 12" vertical reach