

**Little
Giant**
Ladder Systems

CLIMB ON

HYPERLITE[®]



The lightest fiberglass extension ladder in the world

20% to 40% lighter than
comparable extension ladders

Strong Type IA or IAA- rated
ladder tests 20% more rigid† than
comparable extension ladders

Little Giant's patent-pending
Hi-Viz Green is one of the most
visible color hues to the human
eye

**PROUDLY
DESIGNED
ENGINEERED
& MADE IN THE
USA**



**NONCONDUCTIVE
FIBERGLASS
SIDE RAILS**





Little Giant's patent-pending Hi-Viz Green



Side-mounted double-pulley reduces force required to raise the ladder and removes potential tripping hazard



Patented Claw® fastening system clamps the ladder to an overhead anchor point or strand



Patent-pending Sure-Set™ feet stay where you want them (IAA Only)



HyperLite is 20% to 40% lighter than comparable extension ladders

Ordinary extension ladders are heavy. The leading cause of extension ladder injury is linked to the weight of the ladder—often resulting in torn rotator cuffs, herniated disks, ankle sprains and knee ligament tears from loading and unloading or carrying heavy traditional extension ladders. These injuries have simply been part of using extension ladders, until now.

1-YEAR LIMITED WARRANTY
 Available in Type IA, 300 lbs
 Type IAA, 375 lbs duty ratings
**Based on tests performed in controlled ANSI-compliant testing lab.*

Part Number	Description	Highest Standing Level	Max Reach*	Triangle Rung Width	Storage Height	Storage Width	Weight
18716	16' Type IA	9' 5"	15' 11"	1.5"	8' 8"	1' 4.5"	31 lbs
18316	16' Type IA Claw, Cable Hooks & Pole Strap**	9' 5"	15' 11"	1.5"	8' 8"	1' 4.5"	37 lbs
17916	16' Type IAA	9' 5"	15' 11"	1.5"	8' 8"	1' 4.5"	31 lbs
17516	16' Type IAA Claw, Cable Hooks & Pole Strap**	9' 5"	15' 11"	1.5"	8' 8"	1' 4.5"	37 lbs
18720	20' Type IA	13' 3"	19' 9"	1.5"	10' 7"	1' 4.5"	39 lbs
18320	20' Type IA Claw, Cable Hooks & Pole Strap**	13' 3"	19' 9"	1.5"	10' 7"	1' 4.5"	44 lbs
17920	20' Type IAA	13' 3"	19' 9"	1.5"	10' 7"	1' 4.5"	39 lbs
17520	20' Type IAA Claw, Cable Hooks & Pole Strap**	13' 3"	19' 9"	1.5"	10' 7"	1' 4.5"	44 lbs
18724	24' Type IA	17' 1"	23' 7"	1.5"	12' 6.5"	1' 4.5"	45 lbs
18324	24' Type IA Claw, Cable Hooks & Pole Strap**	17' 1"	23' 7"	1.5"	12' 6.5"	1' 4.5"	49 lbs
17924	24' Type IAA	17' 1"	23' 7"	1.5"	12' 6.5"	1' 4.5"	45 lbs
17524	24' Type IAA Claw, Cable Hooks & Pole Strap**	17' 1"	23' 7"	1.5"	12' 6.5"	1' 4.5"	49 lbs
18728	28' Type IA	20' 11"	27' 5"	1.5"	14' 6.5"	1' 4.5"	52 lbs
18328	28' Type IA Claw, Cable Hooks & Pole Strap**	20' 11"	27' 5"	1.5"	14' 6.5"	1' 4.5"	55 lbs
17928	28' Type IAA	20' 11"	27' 5"	1.5"	14' 6.5"	1' 4.5"	52 lbs
17528	28' Type IAA Claw, Cable Hooks & Pole Strap**	20' 11"	27' 5"	1.5"	14' 6.5"	1' 4.5"	55 lbs
18732	32' Type IA	24' 9"	31' 2"	1.5"	16' 6"	1' 4.5"	63 lbs
18332	32' Type IA Claw, Cable Hooks & Pole Strap**	24' 9"	31' 2"	1.5"	16' 6"	1' 4.5"	69 lbs
17932	32' Type IAA	24' 9"	31' 2"	1.5"	16' 6"	1' 4.5"	63 lbs
17532	32' Type IAA Claw, Cable Hooks & Pole Strap**	24' 9"	31' 2"	1.5"	16' 6"	1' 4.5"	69 lbs
17736	36' Type IA	27' 7"	34' 1"	1.5"	18' 5"	1' 4.5"	70 lbs
17336	36' Type IA Claw, Cable Hooks & Pole Strap**	27' 7"	34' 1"	1.5"	18' 5"	1' 4.5"	73 lbs
17740	40' Type IA	30' 5"	36' 11"	1.5"	20' 4.5"	1' 4.5"	77 lbs
17340	40' Type IA Claw, Cable Hooks & Pole Strap**	30' 5"	36' 11"	1.5"	20' 4.5"	1' 4.5"	80 lbs

*A 5' 6" person with a 12" vertical reach
 **Add V to end of the part number to replace the Pole Strap with a V-bar
 Complies with all OSHA, ANSI A14 strength and testing standards. Rung/step spacing complies to OSHA and Int'l standards.
 *OSHA 1910.23, OSHA 1926.10.53, CSA Z11, EN131-1, AS/NZS 1892.2.6.2

*Storage Depth 6"