

**Little
Giant**
Ladder Systems

CLIMB ON



The award winning, lightest fiberglass extension ladder in the world

20% to 40% lighter than
comparable extension ladders

Strong Type IA or IAA- rated
ladder tests 20% more rigid† than
comparable extension ladders

Little Giant's patent-pending
Hi-Viz Green is one of the most
visible color hues to the human
eye



NONCONDUCTIVE
FIBERGLASS
SIDE RAILS





Little Giant's patent-pending Hi-Viz Green



Wide-stance levelers adapt to uneven surfaces and increase side-tip stability up to 600%*



Patent-pending Sure-Set™ Feet (IAA Only) Stays in position when you set it to either flat or spike position



Claw® fastening system clamps the ladder to an overhead anchor point or strand



Side-mounted double-pulley reduces force required to raise the ladder and remove potential tripping hazard

The HyperLite™ SumoStance® is the only extension ladder in the world with Little Giant's patented SumoStance® wide-base levelers, which more than doubles the ladder's base width and increases side-tip stability by up to 600 percent. The SumoStance's intuitive safety features help ensure a safe, stable set-up for any job on almost any surface and is lighter than any other manufacturer's ordinary extension ladders.

1-YEAR LIMITED WARRANTY

Available in Type IA, 300 lbs
Type IAA, 375 lbs duty ratings
**Based on tests performed in controlled ANSI-compliant testing lab.*

Part Number	Description	Highest Standing Level	Max Reach*	Triangle Rung Width	Storage Height	Storage Width	Weight
18816	16' Type IA	9' 6"	16'	1.5"	8' 8"	1' 10.5"	41 lbs
18416	16' Type IA Claw, Cable Hooks & Pole Strap**	9' 6"	16'	1.5"	8' 8"	1' 10.5"	44 lbs
17216	16' Type IAA	9' 6"	16'	1.5"	8' 8"	1' 10.5"	41 lbs
17616	16' Type IAA Claw, Cable Hooks & Pole Strap**	9' 6"	16'	1.5"	8' 8"	1' 10.5"	44 lbs
18820	20' Type IA	13' 4"	19' 10"	1.5"	10' 7"	1' 10.5"	47 lbs
18420	20' Type IA Claw, Cable Hooks & Pole Strap**	13' 4"	19' 10"	1.5"	10' 7"	1' 10.5"	50 lbs
17220	20' Type IAA	13' 4"	19' 10"	1.5"	10' 7"	1' 10.5"	47 lbs
17620	20' Type IAA Claw, Cable Hooks & Pole Strap**	13' 4"	19' 10"	1.5"	10' 7"	1' 10.5"	50 lbs
18824	24' Type IA	17' 2"	23' 8"	1.5"	12' 6.5"	1' 10.5"	54 lbs
18424	24' Type IA Claw, Cable Hooks & Pole Strap**	17' 2"	23' 8"	1.5"	12' 6.5"	1' 10.5"	58 lbs
17224	24' Type IAA	17' 2"	23' 8"	1.5"	12' 6.5"	1' 10.5"	54 lbs
17624	24' Type IAA Claw, Cable Hooks & Pole Strap**	17' 2"	23' 8"	1.5"	12' 6.5"	1' 10.5"	58 lbs
18828	28' Type IA	20' 10"	27' 4"	1.5"	14' 6.5"	1' 10.5"	61 lbs
18428	28' Type IA Claw, Cable Hooks & Pole Strap**	20' 10"	27' 4"	1.5"	14' 6.5"	1' 10.5"	65 lbs
17228	28' Type IAA	20' 10"	27' 4"	1.5"	14' 6.5"	1' 10.5"	61 lbs
17628	28' Type IAA Claw, Cable Hooks & Pole Strap**	20' 10"	27' 4"	1.5"	14' 6.5"	1' 10.5"	65 lbs
18832	32' Type IA	24' 10"	31' 4"	1.5"	16' 6"	1' 10.5"	73 lbs
18432	32' Type IA Claw, Cable Hooks & Pole Strap**	24' 10"	31' 4"	1.5"	16' 6"	1' 10.5"	76 lbs
17232	32' Type IAA	24' 10"	31' 4"	1.5"	16' 6"	1' 10.5"	73 lbs
17632	32' Type IAA Claw, Cable Hooks & Pole Strap**	24' 10"	31' 4"	1.5"	16' 6"	1' 10.5"	76 lbs
17836	36' Type IA	27' 8"	34' 2"	1.5"	18' 5"	1' 10.5"	74 lbs
17436	36' Type IA Claw, Cable Hooks & Pole Strap**	27' 8"	34' 2"	1.5"	18' 5"	1' 10.5"	81 lbs
17840	40' Type IA	30' 6"	37'	1.5"	20' 4.5"	1' 10.5"	81 lbs
17440	40' Type IA Claw, Cable Hooks & Pole Strap**	30' 6"	37'	1.5"	20' 4.5"	1' 10.5"	89 lbs

*A 5' 6" person with a 12" vertical reach
**Add V to end of the part number to replace the Pole Strap with a V-bar
Complies with all OSHA, ANSI A14 strength and testing standards. Rung/step spacing complies to OSHA and Int'l standards.
*OSHA 1910.23, OSHA 1926.10.53, CSA Z11, EN131-1, AS/NZS 1892.2.6.2

* Storage Depth 6"