

**Little
Giant**
Ladder Systems

CLIMB ON



The award winning, lightest fiberglass extension ladder in the world

20% to 40% lighter than
comparable extension ladders

Strong Type IA or IAA- rated
ladder tests 20% more rigid† than
comparable extension ladders

Little Giant's patent-pending
Hi-Viz Green is one of the most
visible color hues to the human
eye



NONCONDUCTIVE
FIBERGLASS
SIDE RAILS





Little Giant's patent-pending Hi-Viz Green



Wide-stance levelers adapt to uneven surfaces and increase side-tip stability up to 600%*



Patent-pending Sure-Set™ Feet (IAA Only) Stays in position when you set it to either flat or spike position



Claw® fastening system clamps the ladder to an overhead anchor point or strand



Side-mounted double-pulley reduces force required to raise the ladder and remove potential tripping hazard

The HyperLite™ SumoStance® is the only extension ladder in the world with Little Giant's patented SumoStance® wide-base levelers, which more than doubles the ladder's base width and increases side-tip stability by up to 600 percent. The SumoStance's intuitive safety features help ensure a safe, stable set-up for any job on almost any surface and is lighter than any other manufacturer's ordinary extension ladders.

1-YEAR LIMITED WARRANTY

Available in Type IA, 300 lbs
Type IAA, 375 lbs duty ratings
**Based on tests performed in controlled ANSI-compliant testing lab.*

| Part Number | Description | Highest Standing Level | Max Reach* | Triangle Rung Width | Storage Height | Storage Width | Weight |
|-------------|---|------------------------|------------|---------------------|----------------|---------------|--------|
| 18816 | 16' Type IA | 9' 6" | 16' | 1.5" | 8' 8" | 1' 10.5" | 41 lbs |
| 18416 | 16' Type IA Claw, Cable Hooks & Pole Strap** | 9' 6" | 16' | 1.5" | 8' 8" | 1' 10.5" | 44 lbs |
| 17216 | 16' Type IAA | 9' 6" | 16' | 1.5" | 8' 8" | 1' 10.5" | 41 lbs |
| 17616 | 16' Type IAA Claw, Cable Hooks & Pole Strap** | 9' 6" | 16' | 1.5" | 8' 8" | 1' 10.5" | 44 lbs |
| 18820 | 20' Type IA | 13' 4" | 19' 10" | 1.5" | 10' 7" | 1' 10.5" | 47 lbs |
| 18420 | 20' Type IA Claw, Cable Hooks & Pole Strap** | 13' 4" | 19' 10" | 1.5" | 10' 7" | 1' 10.5" | 50 lbs |
| 17220 | 20' Type IAA | 13' 4" | 19' 10" | 1.5" | 10' 7" | 1' 10.5" | 47 lbs |
| 17620 | 20' Type IAA Claw, Cable Hooks & Pole Strap** | 13' 4" | 19' 10" | 1.5" | 10' 7" | 1' 10.5" | 50 lbs |
| 18824 | 24' Type IA | 17' 2" | 23' 8" | 1.5" | 12' 6.5" | 1' 10.5" | 54 lbs |
| 18424 | 24' Type IA Claw, Cable Hooks & Pole Strap** | 17' 2" | 23' 8" | 1.5" | 12' 6.5" | 1' 10.5" | 58 lbs |
| 17224 | 24' Type IAA | 17' 2" | 23' 8" | 1.5" | 12' 6.5" | 1' 10.5" | 54 lbs |
| 17624 | 24' Type IAA Claw, Cable Hooks & Pole Strap** | 17' 2" | 23' 8" | 1.5" | 12' 6.5" | 1' 10.5" | 58 lbs |
| 18828 | 28' Type IA | 20' 10" | 27' 4" | 1.5" | 14' 6.5" | 1' 10.5" | 61 lbs |
| 18428 | 28' Type IA Claw, Cable Hooks & Pole Strap** | 20' 10" | 27' 4" | 1.5" | 14' 6.5" | 1' 10.5" | 65 lbs |
| 17228 | 28' Type IAA | 20' 10" | 27' 4" | 1.5" | 14' 6.5" | 1' 10.5" | 61 lbs |
| 17628 | 28' Type IAA Claw, Cable Hooks & Pole Strap** | 20' 10" | 27' 4" | 1.5" | 14' 6.5" | 1' 10.5" | 65 lbs |
| 18832 | 32' Type IA | 24' 10" | 31' 4" | 1.5" | 16' 6" | 1' 10.5" | 73 lbs |
| 18432 | 32' Type IA Claw, Cable Hooks & Pole Strap** | 24' 10" | 31' 4" | 1.5" | 16' 6" | 1' 10.5" | 76 lbs |
| 17232 | 32' Type IAA | 24' 10" | 31' 4" | 1.5" | 16' 6" | 1' 10.5" | 73 lbs |
| 17632 | 32' Type IAA Claw, Cable Hooks & Pole Strap** | 24' 10" | 31' 4" | 1.5" | 16' 6" | 1' 10.5" | 76 lbs |
| 17836 | 36' Type IA | 27' 8" | 34' 2" | 1.5" | 18' 5" | 1' 10.5" | 74 lbs |
| 17436 | 36' Type IA Claw, Cable Hooks & Pole Strap** | 27' 8" | 34' 2" | 1.5" | 18' 5" | 1' 10.5" | 81 lbs |
| 17840 | 40' Type IA | 30' 6" | 37' | 1.5" | 20' 4.5" | 1' 10.5" | 81 lbs |
| 17440 | 40' Type IA Claw, Cable Hooks & Pole Strap** | 30' 6" | 37' | 1.5" | 20' 4.5" | 1' 10.5" | 89 lbs |

*A 5' 6" person with a 12" vertical reach

**Add V to end of the part number to replace the Pole Strap with a V-bar

Complies with all OSHA, ANSI A14 strength and testing standards. Rung/step spacing complies to OSHA and Int'l standards.*

*OSHA 1910.23, OSHA 1926.10.53, CSA Z11, EN131-1, AS/NZS 1892.2.6.2

• Storage Depth 6"