

2', 4', 6', 8', & 10'

OSHA & ANSI COMPLIANT ENCLOSED SAFETY CAGE

1. STABLE, FULLY ENCLOSED CLIMBING SOLUTION

The OSHA-compliant Safety Cage eliminates the need to tie-off, helping you get your work done quickly, making it the ideal climbing alternative for the job site.

2. EASY TO USE, STORE AND CARRY

The Safety Cage can be set up and taken down with just one person, and with its compact folding capabilities, storage is easy. Tip & Glide wheels lighten the load for transport. With caster wheel lifts you can roll the Cage from place to place, even while fully deployed.

3. NON-CONDUCTIVE, HI-VIZ GREEN FIBERGLASS

Our Hi-Viz green fiberglass is lightweight and non-conductive. The color is proven to increase visibility, preventing injuries and accidents while in use.

4. GROUND CUE[®]

Up to 20% of all ladder injuries happen from missing the bottom step while descending the ladder. Ground Cue makes an audible and tactile "click" that alerts you when you've reached the bottom rung.

5. ADJUSTABLE OUTRIGGERS[®]

Adjustable Outriggers provide increased side-tip stability while using the cage.



 NON-CONDUCTIVE FIBERGLASS
FIBRA DE VIDRIO NO CONDUCTORA





Ground Cue® Bottom Rung Alerts



Move a Deployed Ladder with Wheel Lift Casters



Tip & Glide™ Wheels Increase Transportation



Large Standing Platform



Enclosure Eliminates Tie-off Requirement



Outrigger Stability

PRODUCT DESCRIPTION

It's not a ladder, it's the Little Giant® Safety Cage®. With the Cage, you can access workspaces that would typically require tying-off, scaffolding or lifts, all with less time and labor than other climbing solutions. The Cage has a comfortable standing surface with a fully enclosed toe kick and wraparound enclosure, making it faster, safer and less expensive than many scaffolding or lift options. Plus, because you can work hands-free, the Safety Cage is perfect for jobs like maintaining large HVAC equipment or installing stage lighting.

1-YEAR LIMITED WARRANTY

Part #	Model	Comparable Step Ladder Size	Highest Standing Level	Max Reach*	Spread	Storage Width at Base	Weight
19702	2'	4'	1' 10"	8' 4"	2' 10"	2' 3"	45 lbs
19704-146	4'	6'	3' 8"	10' 2"	3' 11"	2' 11"	54 lbs
19706-146	6'	8'	5' 7"	12' 1"	5' 1"	3' 2"	65 lbs
19708-146	8'	10'	7' 5"	13' 11"	6' 3"	3' 5"	69 lbs
19710-146	10'	12'	9' 4"	15' 10"	7' 5"	3' 8"	81 lbs

*A 5' 6" person with a 12" vertical reach · The 2' model does not include outriggers · The 10' model is Type IA 300 lbs rated